

## BETA 15C (4 ohm version)

Nominal Basket Diameter	15", 381mm
Impedance	4 ohms
Power Rating	350Wrms
Resonance	33Hz
Usable Frequency Range	35Hz - 4kHz
Sensitivity	<a href="#">see guide on web</a>
Magnet Weight	34oz.
Gap Height	0.312", 7.94mm
Voice Coil Diameter	2", 50.8mm

### Mounting Information

Recommended Enclosure Volume (vented)	106 - 177 liters 3.75 - 6.25 cu. ft.
Overall Diameter	15.15", 384.8mm
Baffle Hole Diameter	13.77", 349.6mm <i>fitted as standard</i>
Front Sealing Gasket	<i>fitted as standard</i>
Rear Sealing Gasket	
Mounting Holes Diameter	0.25", 6.4mm
Mounting Holes B.C.D.	14.56", 369.9mm
Depth	6.05", 153.6mm
Shipping Weight	11lbs., 5 kg.

### Thiele-Small Parameters

Resonant Frequency (fs)	33Hz
Impedance (Re)	3.09 ohms
Coil Inductance (Le)	0.75mH
Electromagnetic Q (Qes)	0.51
Mechanical Q (Qms)	6.07
Total Q (Qts)	0.47
Compliance Equivalent Volume (Vas)	333 liters 11.76 cu. ft.
Mechanical Compliance of Suspension (Cms)	0.35mm/N
BL Product (BL)	9.15 T-M
Diaphragm Mass inc. Airload (Mms)	67 grams
Equiv. Resistance of Mechanical Suspension Loss (Rms)	2.29N*sec/M
Efficiency Bandwidth Product (EBP)	64
Voice Coil Overhang (Xmax)	4.0mm
Surface Area of Cone (Sd)	823.7cm <sup>2</sup>



### Application Notes

For all high power bass applications including bass guitar.

### Materials of Construction

- Kapton coil former for increased rigidity and thermal protection
- Polyamide-imide coated two-layer, 28ga., copper voice coil for improved power handling and durability.
- Ferrite Magnet
- Vented core for increased power handling
- Premium pressed steel basket for maximum strength
- Paper cone
- Cloth cone edge
- Solid composition paper dust cap

**Eminence Speaker LLC**  
**P. O. Box 360**  
**Eminence, Kentucky 40019**  
**USA**  
**502.845.5622 phone**  
**502.845.5653 fax**  
**info@eminence.com**  
**www.eminence.com**