Blue Tick Hound"

blü' tik' haünd' n. a smooth, well balanced 12" American guitar speaker, fast to break up

Impedance
Power Rating**
Voice Coil Diameter
Coil Material
Flat/Round Coil Wire
Coil Former Material
Basket Type
Cone Surround Material
Dust Cap Material
Magnet Weight
Usable Bandwidth (Fs to -3dB)
SPL*

8 ohms
75Wrms/150W peak**
1.5", 38.1mm
Copper
Round
Kapton
Stamped
Paper
Zurette
20oz.
70Hz - 4.5kHz
99dB*



Mounting Information

Nominal Basket Diameter Baffle Hole Diameter Mounting Holes Diameter Mounting Holes B.C.D. Depth Shipping Weight 12.24", 310.9mm 11.04", 280.4mm 0.25", 6.4mm 11.63", 295.3mm 4.4", 111.8mm 7 lbs., 3.2 kg.

Application Notes

"Very smooth, with scooped mids and warm top end. Overall, very smooth and creamy."

Thiele-Small Parameters

Impedance (Re)
Coil Inductance (Le)
Total Q (Qts)
Efficiency Bandwidth Product (EBP)
Voice Coil Overhang (Xmax)
Surface Area of Cone (Sd)

7.64 ohms 0.36mH 1.61 67

67 0.0mm 525.8cm2

- * Published sensitivity is an average of multiple points representing the measured output of the device (1W-1m) across the usable frequency range from 200Hz-5kHz.
- ** EIA 426A noise source and test standard. Eminence voice coil technology often results in guitar speakers that dramatically exceed the power rating of other manufacturer's products. Such ratings are not meant to imply the Eminence woofers are not equally suitable for lower-power "Class A" valve amplifiers as they are for high gain valve and transistor amplification.

Eminence Speaker
P. O. Box 360
Eminence, KY 40019
USA
502.845.5622 phone
502.845.5653 fax
info@eminence.com
www.eminence.com

